

# MOTO SUPER 4T 20W-50



MOTORCYCLE

## Lubricants

### Description

Lubricant oil for 4-strokes engines with an excellent performance. Developed to provide a suitable cleanliness of the engine and protection in all kind of operations. It is suitable for every kind of 4-strokes motorcycles with or without wet clutch.

### Properties

- Its viscosity properties allow a good performance in a wide range of temperatures.
- Formulated to provide optimum protection against metal-to-metal wear and keep the engine clean fighting oil deposits.
- Especially designed to ensure good protection for the engine and the gearbox, preventing wet clutch slippage and increasing its performance.

### Quality levels

- JASO T903:2016: MA2
- API SJ

### Technical specifications

	UNIT	METHOD	VALUE
SAE GRADE			20W-50
Density at 15 °C	g/mL	ASTM D 4052	0.885
Viscosity at 100 °C	cSt	ASTM D 445	18.4
Viscosity at 40 °C	cSt	ASTM D 445	171
Viscosity at -20 °C	cP	ASTM D 5293	9500 max.
Viscosity index	-	ASTM D 2270	121
Flash point, open cup	°C	ASTM D 92	230
Pour point	°C	ASTM D 97	-15 max.
T. B. N.	mg KOH/g	ASTM D 2896	6

The above mentioned characteristics are typical values and should not be considered product specifications.

A safety information file is available on request.

repsol.com  
+34 901 111 999  
lubricantes@repsol.com

Technical data sheet for Lubricant RNG200. Revision 1. March 2020.